









# GAMA LIGERA CARB

# 4 HP



	F4BML	F4BMS	F4ABML	F4ABMS
A (mm)	717 (28.2")		717 (28.2")	
B (mm)	361 (14.2")		390 (15.4")	
C (mm)	1.156 (45.5")	1.029 (40.5")	1.177 (46.3")	1.050 (41.3")
D (mm)	508 (20.0")	381 (15")	508 (20.0")	381 (15")
 Weight (kg)	25.5 kg	24.5 kg	28 kg	27 kg

		4 HP			
		F4BML	F4BMS	F4ABML	F4ABMS
Régimen de trabajo a pleno gas	Full throttle operating range	4.500 - 5.500 rpm		4.500 - 5.500 rpm	
Potencia máxima	Maximum output	2.9 Kw (4 Hp) 4.500 rpm		2.9 Kw (4 Hp) 5.000 rpm	
Ralentí (neutral)	Idling speed (neutral)	1.450 - 1.550 rpm		1.450 - 1.550 rpm	
Tipo motor	Engine type	OHV		OHV	
Cilindros	Cylinders	1		1	
Cilindrada	Displacement	112 cm <sup>3</sup>		148 cm <sup>3</sup>	
Diámetro por carrera	Bore per stroke	59 x 41 mm (2.32" x 1.61")		64 x 46 mm (2.52" x 1.8")	
Sistema de encendido	Ignition system	TCI		CDI	
Alternador	Alternator			12V 6A	
Sistema de control	Control system				
Sistema de arranque	Starting system				
Cambio de marchas	Gear positions	<b>F - N - R</b>		<b>F - N - R</b>	
Relación engranajes	Gear ratio	2.15 (28/13)		2.15 (28/13)	
Sistema inclinación y elevación	Trim & tilt system				
Consumo máximo	Maximum fuel waste	1.6 L/h		1.8 L/h	
Depósito combustible	Fuel tank capacity	1.3 L		1.3 L	
Capacidad aceite motor	Engine oil capacity	0.5 L		0.8 L	
Capacidad aceite caja engranajes	Gear oil capacity	100 cm <sup>3</sup>		195 cm <sup>3</sup>	
Hélice STD incluida	Included STD Propeller	3-71/2" x 7"		3-71/8" x 9"	

## ACCESORIOS INCLUIDOS INCLUDED ACCESSORIES

		UN.
Manual de uso	Owner manual	1
Hombre al agua	Stoper, hang rope assy	1
Tirador cuerda arranque	Emergency handle-start rope	1
Destornillador	Screwdriver	1
Bujías	Spark plug	1
Extrator bujías	Spark plug sleeve	1
Pasador hélice	Pin, cotter	1