


GAMA LIGERA CARB

9.8 - 8 HP



		9.8 HP			8 HP		
		F9.8BML	F9.8BMS	F9.8FWL	F8BML	F8BMS	F8FWL
	A (mm)	965 (38")			965 (38")		
	B (mm)	364 (14.3")			364 (14.3")		
	C (mm)	1.166 (45.9")	1.039 (40.9")	1.166 (45.9")	1.166 (45.9")	1.039 (40.9")	1.166 (45.9")
	D (mm)	508 (20")	381 (15")	508 (20.0")	508 (20.0")	381 (15")	508 (20.0")
	Weight (kg)	39.5 kg	38 kg	42.5 kg	39.5 kg	38 kg	42.5 kg
Régimen de trabajo a pleno gas	Full throttle operating range	5.000 - 6.000 rpm			5.000 - 6.000 rpm		
Potencia máxima	Maximum output	7.2 Kw			5.9 Kw		
Ralentí (neutral)	Idling speed (neutral)	900 - 1.000 rpm			900 - 1.000 rpm		
Tipo motor	Engine type	SOHC			SOHC		
Cilindros	Cylinders	L2			L2		
Cilindrada	Displacement	209 cm ³			209 cm ³		
Diámetro por carrera	Bore per stroke	55 x 44 mm (2.17" x 1.73")			55 x 44 mm (2.17" x 1.73")		
Sistema de encendido	Ignition system	CDI			CDI		
Alternador	Alternator	12V 6A			12V 6A		
Sistema de control	Control system						
Sistema de arranque	Starting system						
Cambio de marchas	Gear positions	F - N - R			F - N - R		
Relación engranajes	Gear ratio	2.00 (26/13)			2.00 (26/13)		
Sistema inclinación y elevación	Trim & tilt system						
Consumo máximo	Maximum fuel waste	3.4 L/h			2.8 L/h		
Depósito combustible	Fuel tank capacity	12 L			12 L		
Capacidad aceite motor	Engine oil capacity	0.8 L			0.8 L		
Capacidad aceite caja engranajes	Gear oil capacity	320 cm ³			320 cm ³		
Hélice STD incluida	Included STD Propeller	3-8.9" x 8.3"			3-8.9" x 8.3"		

ACCESORIOS INCLUIDOS INCLUDED ACCESSORIES

		UN.
Manual de uso	Owner manual	1
Hombre al agua	Stoper, hang rope assy	1
Tirador cuerda arranque	Emergency handle-start rope	1
Destornillador	Screwdriver	1
Bujías	Spark plug	2
Extrator bujías	Spark plug sleeve	1
Pasador hélice	Pin, cotter	1
Línea combustible	Fuel line assy	1
Depósito combustible	Fuel tank assy	1